



## .308 Win. SWISS P AP

7.62 mm x 51

- Compatible with all 7.62 x 51 mm bolt action weapons
- Unique combination of excellent accuracy with maximum penetration
- Same trajectory as Ball/Styx Action/Target



### Application:

Maximum penetration to overcome armoured targets which are protected by vests, bulletproof glass, light armour, and other cover. The SWISS P projectile with a tungsten carbide penetrator of a new design

(patented bullet) will defeat armour targets, even at a long range. With matching trajectory, the SWISS P Armour Piercing cartridge will penetrate the hardened target with precision fire.



### Cartridge Data

weight:	27 g
case material:	CuZn - alloy
primer:	large rifle
propellant:	single base
projectile:	FMJHC
ballistic coefficient C1:	0.625 (ICAO)
projectile weight:	196 grs / 12.7 g
jacket material:	CuZn - alloy
core material:	WCCo + PbSb - alloy
dimensions:	in accordance with CIP
marking:	black tip



### Technical Data

temperature range:	between -54°C and +52°C
muzzle velocity:	min. 810 m/s
mean chamber pressure:	max. 4000 bar
accuracy 100 m:	100% radius 21 mm, 10 rounds
accuracy 300 m:	100 % radius 63 mm, 10 rounds
penetration 150 m:	12 mm steel + 21 layers kevlar at an angle of 0°
penetration 300 m:	body armour class 4++ at an angle of 0°

NSN:	1305-22-266-0523
Packaging and Marking:	In accordance with customers' requirements
	Errors and technical changes excepted

## RUAG Ammotec

Uttigenstrasse 67 · CH-3602 Thun · Switzerland

Tel. +41 332 282 879, Fax +41 332 282 644 · sales.ammotec@ruag.com · www.ruag.com