



.338 Lapua Mag. SWISS P Tactical

8.6 mm x 70

- No deflection when shooting through glass at up to 30°
- Same trajectory as AP / Ball / Target / Styx Action up to 300 m
- Solid projectile does not splinter



Application:

Thanks to its specially shaped profile, the SWISS P Tactical is ideal for combating targets behind glass. Shooting through laminated glass (windscreens etc.) at angles up

to 30° causes only very slight trajectory deflection. The SWISS P Tactical uses a solid tombak projectile which does not splinter, thus minimizing risk to third parties.



Cartridge Data

weight:	44 g
case material:	CuZn - alloy
primer:	large rifle
propellant:	double base
projectile:	solid FNBT
ballistic coefficient C1:	0.390 (ICAO)
projectile weight:	250 grs / 16.2 g
jacket material:	CuZn - alloy
core material:	CuZn - alloy
dimension:	in accordance with CIP



Technical Data

temperature range:	between -54°C and +52 °C
muzzle velocity:	min. 860 m/s (test barrel 650 mm)
mean chamber pressure:	max. 4200 bar (P _T)
accuracy 300 m:	100% radius 48 mm, 10 rounds

Packaging and Marking:	In accordance with customers' requirements
	Errors and technical changes excepted

RUAG Ammotec

Uttigenstrasse 67 · CH-3602 Thun · Switzerland

Tel. +41 332 282 879, Fax +41 332 282 644 · sales.ammotec@ruag.com · www.ruag.com